



OKAI RANGER



Motor Parameter	Rated Power: 750W Max Power: 1000W	Charger	Input Voltage: 100-240V Output Voltage: 54.6V Output Current: 2.8A
Battery Parameter	Battery Capacity: 48V 14.7Ah Cell Qty: 39PCS Charging Time: < 6H	Brake	Front: Mechanical Disc Brake Rear: Mechanical Disc Brake Braking Distance: ≤ 33ft Brake Response Time: 0.1 second
Rider	Max Load: 330lbs Required Height: 5.1-6.6ft	Tire	Size: 26 inches
Product Weight	Net Weight: 84lbs	Light	12V 2.5W LED Head & Tail Light
Product Parameter	Material: 6000-Series Aircraft-Grade Aluminum Frame Range (Throttle): Up to 30 Miles Range (Pedal Assist): Up to 45 Miles Max Torque: 85N.m Waterproof Grade: IPX5 Adapted Terrain: Flat and Mountainous Terrain Ride Mode: 5 Modes with Rear Drive Handles: Anti-Slip Seat: Adjustable Seat Height	Certification	Bicycle: CPSC 16 CFR 1512, UL2849 Test Report, 16 CFR 1303&Prop 65 Test Report; Battery: UL 2271; Battery Charger: UL 1012; Motor Control: UL 2849;

Logistic Information

UPC Code

Product

OKAI EB50 US BLUE

OKAI EB50 US BLACK

UPC

810100340056

608938951908

Package Info.

Carton Dimension:

61.46*14.76*33.62inch

Net Weight: 83.78 lbs

Gross Weight: 100.31lbs

In Box Info.

OKAI EB50

Folding Keys

Toolkit

Headlight

Charger

Instruction Book

Pump

Pedals

Quick Release

Reflector

Front and Back Fenders